
V 386 MF


Silver Oxide / Zinc

Data Sheet



Type Number	20386
Designation IEC	SR1142W (SR43)
System	Silver Oxide / Zinc / KOH - Electrolyte
Nominal Voltage	1,55 V
Typical Capacity C	115 mAh
Load 5.6 kOhm, at 20°C down to 1.2 V	
Weight (approx.)	1,56 g
Volume	0,39 ccm
Coding	Date of Manufacturing Month/Year





Temperature Ranges	min	max.
Storage	0°C	60°C
Discharge	0°C	60°C*

Dimensions	min	max.
Diameter (A)	11,25	11,60
Height (B)	3,80	4,20
Shoulder Diameter[E]	6,00	
Shoulder Height [C]	0,08	

Typical Capacities (at 20°C)

Discharge Type	Load	End Voltage:	1.2 V
Continuous	5600 Ω	Time:	430 h
24h/d,7d/w		Capacity [mAh]:	115
Current [µA]:		Energy [mWh]:	170

* Contact VARTA if the application is intended to be outside the range of 0°C to +60°C.

Information and contents in this data sheet are for reference purpose only.
They do not constitute any warranty or representation and are subject to change without notice.
For most current information and further details, please contact your VARTA representative.

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553

Subject to change without prior notice!

Date of issue: 2015-02-16