Data Sheet



Type Number	20379
Designation IEC	SR521SW (SR63)
System	Silver Oxide / Zinc / NaOH - Electrolyte
Nominal Voltage	1,55 V
Typical Capacity C	15 mAh
Load 68,1 kOhm, at 20°C down to 1.2 V	
Weight (approx.)	0,23 g
Volume	0,06 ccm
Coding	Date of Manufacturing Month/Year

Temperature Ranges	min	max.
Storage	0°C	60°C
Discharge	0°C	60°C*

Dimensions	min	max.
Diameter (A)	5,65	5,80
Height (B)	1,95	2,15
Shoulder Diameter[E]	2,60	
Shoulder Height [C]	0,06	

Typical Capacities (at 20°C)

Discharge Type	**Load**	**End Voltage:**	**1.2 V**
Continuous	68100 Ω	Time:	665 h
24h/d,7d/w		Capacity [mAh]:	15
Current [µA]:		Energy [mWh]:	24

* Contact VARTA if the application is intended to be outside the range of 0°C to +60°C.

Information and contents in this data sheet are for reference purpose only.
They do not constitute any warranty or representation and are subject to change without notice.
For most current information and further details, please contact your VARTA representative.

VARTA Microbattery GmbH, Daimlerstr. 1, D-73479 Ellwangen/Jagst
Tel.: (+49) 7961/921-0, Telefax: (+49) 7961/921-553
Subject to change without prior notice!
Date of issue: 2014-12-12