

battery type:			Lithium Button Cell
battery size:			CR3032
chemical system:			Lithium Manganese Dioxide
			Conditions
nominal voltage:	3.0	V	
open circuit voltage:	3.0...3.4	V	new battery
	2.9...3.4	V	after 1 year storage at 20°C
			all measurements at 22 ± 2°C ambient
capacity			
rated:	500	mAh	continuous discharge at 7.5kΩ load; 24hours/day End Voltage (EV): 2.0V
minimum:	450	mAh	continuous discharge at 7.5kΩ load; 24hours/day EV: 2.0V
standard discharge time			
minimum:	150	h	at 1.2kΩ load (for QC measurement) EV: 2.0V
discharge currents			
standard:	0.2	mA	
max. recommended current under continuous discharge:	5	mA	
max. recommended current under pulse discharge:	20	mA	

discharge diagrams:

Discharge Characteristics on Load



Discharge Characteristics on Temperature




shelf life:	10	years	under proper storage conditions (ta: ≤ 22°C; RH: 60 ± 15%)
self-discharge:	≤ 2	%	per year (at 20°C ambient temperature)
operating temperature range:	- 20…70	°C	
storage temperature:	0…30	°C	(recommended)

mechanical specifications:

outer battery dimensions

diameter:	30.0mm	+0/-0.3mm
height:	3.2mm	+0/-0.4mm

drawing





printed production date
4 digits (YYMM)
e.g. 1806 = 2018 June

nominal weight:	6.8	g	(approx.)

107

ANSMANN	**ANSMANN Specifications for model:**	**CR3032 Lithium Button Cell bulk package**
	data sheet no. / part no.	1506-0009
	supplier no.	704080
	author / date	TG / 16.03.2021

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice