https://www.mega-piles.com/
+ 44 (0) 208 920 2306
www.energizer-eu.com

ENERGIZER 321

ZERO MERCURY®

SILVER OXIDE




Specifications

Chemical System:	Silver Oxide (Zn/Ag_2O)
Nominal Voltage:	1.55 Volts
Typical Capacity:	15 mAh* (to 1.2 volts)
Capacity Test:	100K ohm continuous drain at 21°C
Typical Weight:	0.28 grams (0.01 oz.)
Typical Volume:	0.07 cubic centimeters (0.004 cubic inch)
Impedance (40 Hz):	30 to 40 ohms


* Varies according to the applied load, temperature, and cutoff voltage.

Industry Standard Dimensions

mm (inches)



Cross Section




DESIGNED FOR USE ON CONTINUOUS LOW DRAIN

Typical Discharge Characteristics

Typical Performance at 21°C (70°F)

Schedule: Continuous
Typical Drain @1.55V:
0.0155 milliamperes
Load: 100K ohm




Schedule	Typical Drains at 1.55V (milliamperes)	Load (ohm)	Cutoff 1.2V (hours)
Continuous	0.0155	100K	970


Temperature Characteristics

Typical Performance at Low Discharge Rates

Service Effects



Storage Effects



Important Notice

This datasheet contains typical information specific to products manufactured at the time of its publication.
©Energizer Holdings, Inc. - Contents herein do not constitute a warranty.